

ALLOW HIGHER PERMEATION

HIGH PRESURE RESISTANCE

HIGH QUALITY
IN TUBING MATERIAL

MADE IN POLAND



TUBE: BLACK LPG RESISTANT SYNTHETIC RUBBER
 REINFORCEMENT: ONE BRAID OF BRASS COATED HIGH TENSILE STEEL WIRE STRANDS (ELECTRICALLY CONDUCTIVE)
 COVER: SYNTHETIC RUBBER WITH HIGH ABRASION, OZONE, WEATHER RESISTANCE, PIN-PERFORATED TO ALLOW EFFUSION OF TRAPPED GASES.
 OPERATING TEMPERATURE RANGE: -40°C TO 120°C INTERMITTANTLY UP TO +150°C

EXTRA FLEXIBLE WIRE BRAID

PRODUCT CODE	HOSE BORE		HOSE O.D.		WIRE O.D.		BEND RADIUS		MAX. W.P.	MIN. W.P.
	(IN.)	(MM.)	(IN.)	(MM.)	(IN.)	(MM.)	(IN.)	(MM.)	(PSI)	(PSI)
54104	1/4	6.40	0.59	15.50	0.437	11.10	2.76	70.00	400	1200

LPG RUBBER HOSE TYPE: LPG 25 W



MEET B.S. 4089 TYPE 2, ECE 67R
 RECOMMENDED FOR ALL STAGES OF LPG

HIGHER ABRASIVE RESISTANCE WITH THICKER WALL THICKNESS / MADE IN POLAND

LPG GAS ASSEMBLY HOSE WITH END FITTINGS				
MODEL	WAWEL-N	WAWEL-W	WAWEL-PTT	WAWEL-U
SPECIFICATION	POL X MNPT 1/4	MNPT X FNPT 1/4	MNPT X MNPT 1/4	MNPT 1/4 X FNPT 1/8
FITTINGS				
STANDARD	B.S. 4089 TYPE 2, ECE 67R			
STANDARD	600 MM., 800 MM., CUSTOM MADE			

